

# SPECIFICATION



บริษัท จีเทคโอเอชเอ็ม จำกัด  
G-TECH OHM CO.,LTD.  
ศูนย์ค้าส่งวัสดุสิ่งไหมชนบทถนน

# KOTEX

Textile Printing Material

## KOTEX-II / CODE : KOTEX-II-X.XX-40M

### APPLICATION

Flag  
Street Banner  
Department store display, Transit Displays  
Metro illuminated signage  
P.O.P. and Display System  
Decorative Exhibition  
Backdrop events, hanging  
Indoor / Outdoor media

### COMPATIBILITY

Ink Compatibility

ECO



Solvent



UV-Curable



Printer Compatibility

Most Solvent & Eco Solvent, UV Curable Printing system : LATEX &  
HP, Agfa-Jeti, Epson, Roland, Mimaki, Mutoh, Seiko, Oce, VUTEK, Scorpion, Keundo, etc.

### SPECIFICATION

Caliper	0.34 mm.
weight	185 g/m <sup>2</sup>
Base material	Polyester
Surface	Matt
Width	1.27, 1.52, 1.82, 2.00, 2.50 m.
Lenght	40 m.
Yarn x Threat	300x300

### TEST RESULTS

Surface	Matt	
FR treatment	Non-FR	
Width (mm)	914	
	1065	
	1270	
	1370	
	1524	
	1800	
	2000	
	2500	
3200		
Compitable Ink	Solvent Eco-Solvent UV Curable	
Core	3"	
Denier	warp	300
	wert	300
Thickness	0.28 mm	
Weight	185 g/m <sup>2</sup>	
Fabric Count (pick/2.54cm)	warp	59
	wert	45
Breaking Strength*	warp	1300
	wert	1000
Tearing Strength*	warp	62.5
	wert	53.2
Colorfastness to light 20 Hrs.*	grade 4	

### GUIDELINES

- Printing Tip :** Dry time will vary depending on ink type.
- Storage :** It is recommended to store in the closed original packing in a cool and dry environment
- Shelf Life :** One year stored in original package in recommended condition

Information provided here is subject to our test criteria and subject to change without prior notice. No media warranty is implied.  
All material should be tested by purchaser to determine final suitability. Printer and ink change may affect results.