



QS3250r

Roll-to-Roll Productivity Meets High-Definition Quality

The VUTEK® QS3250r roll-to-roll UV-curing printer from EFI™ is now part of the award-winning VUTEK QS Family combining High-Definition Print (HDP) capability with high production speeds, making the VUTEK QS3250r ideal for sign shops and commercial printers upgrading to UV output with uncompromised quality and UV roll-to-roll capability. Best of all, it's from VUTEK, the leader in superwide format printing.

The VUTEK DNA makes your business more productive, profitable and successful now and for generations to come. The printer comes with a host of advantages including:

- HDP Print resolutions up to 1080 dpi for dazzling images and sharp text.
- Productivity up to 1,850 square feet (172 square meters) per hour.
- The ability to print on wide variety of flexible substrates up to .125 inches (3mm) thick and 126.5 inches (3.2 meters) wide.
- High quality VUTEK inks.
- Un-paralleled training, service and support, including our
- Enhanced Service program (ESP).*
- EFI Fiery® XF, a production RIP.
- Optional Heavy Duty Unwinder.





QS3250r

VUTEK QS3250r

Features and Benefits

EFI's portfolio of integrated solutions increases productivity and improves your bottom line. Find out more at www.efi.com.

- Eight-color UV printing for outstanding image quality switchable to Fast-4™ for high productivity.
- High Definition, 1080 dpi printing.
- Prints quality output up to 1,850 sq ft/hr (172 sqm/hr).
- High definition image quality.
- VUTEK Smoothing.
- Sturdy production design for around the clock operation.
- No harmful VOC emissions.
- Fully enclosed design for operator safety.

Media/Handling

- Size: sheet and continuous feed, up to 126.5 inches (3.2 meters) wide.
- Type: flexible on roll to roll up to .125 inches (3mm) thick.
- Optional heavy duty unwinder.

Printing Technology

- Seiko drop-on-demand Piezo inkjet technology.
- VUTEK QS3250r: user selectable 540 or 1080 dpi.
- One-year printer warranty (includes parts, labor and Seiko inkjet heads).
- 24 x7 technical support.

Formats

- All popular desktop file formats, including PostScript®3, EPS, TIFF, PDF, RGB/CMYK.

Environmental Considerations

- Compressed Air: 95-150 maximum at 4 cf/m-dry air only (not included).
- Temperature: 68 F to 85 F (20 C to 30 C).
- Humidity: 30% to 80% (non condensing).
- Weight: 7019 lbs (3184 kg).
- Height: 69" (175 cm).
- Width: 232" (590 cm).
- Depth: 67" (169 cm).
- + 15" (38 cm) unwinder.
- + 15" (38 cm) rewinder.
- Electrical: 1-Phse, 70 amp, 200-240 volt supply).

Fiery XF RIP

- Optimized for use with EFI Fiery® XF RIP.
- Advanced, easy-to-use, wizard-guided color tools for consistent, predictable, high quality color.
- Powerful production tools include nesting, step and repeat, scaling, cropping and tiling.
- Advanced ICC color management for reliable color quality output and proofing-quality color.
- Scalable, versatile platform grows with your needs when your business grows.

Inks

- VUTEK Inks are supplied in 5.0 liter containers available in cyan, magenta, yellow, black, light cyan, light magenta, light yellow and light black.

Enhanced Service Plans

Eligible for:

- Critical-eight business hour (one business day) response)*.
- ProActive – 16 business hour (two business day) response*.
- Essential – 24 business hour (three business day) response.*

* where available



One VUTEK Place
Meredith, NH 03253
603-279-4635
www.efi.com/VUTEK

Auto-Count, Bliss, Changing the Way the World Prints, ColorWise, Command WorkStation, DocBuilder, DocBuilder Pro, DocStream, EDOX, EFI, Fiery, the Fiery logo, Fiery Driven, the Fiery Driven logo, OneFlow, PrinterSite, PrintFlow, PrintMe, PrintSmith Site, Prograph, Proteus, RIP-While-Print, Setting the Standard in Digital Printing, Ultravu and VUTEK are registered trademarks of Electronics for Imaging, Inc. in the U.S. Patent and Trademark Office and/or certain other foreign jurisdictions. Bestcolor is a registered trademark of Electronics For Imaging GmbH in the U.S. Patent and Trademark Office. AutoCal, Balance, BioVu, BioWare, Build, ColorCal, Digital StoreFront, Estimate, Fiery Link, Fiery Prints, Fiery Spark, FreeForm, Hagen, Jettron, Logic, MicroPress, PhotoXposure, PrintCafe, PrintSmith, PSI, PSI Flexo, RemoteProof, RIPChips, Scan, Screenproof, SendMe, Splash, Spot-On, UltraTex, UV Series 50, VisualCal, WebTools, the EFI logo, the Fiery Prints logo and Essential to Print are trademarks of Electronics for Imaging, Inc. Best, the Best logo, Colorproof, PhotoXposure, RemoteProof, and Screenproof are trademarks of Electronics For Imaging GmbH. All other terms and product names may be trademarks or registered trademarks of their respective owners, and are hereby acknowledged. © 2009 Electronics for Imaging.

VTKQS3250r DS 09/20/09



Superwide Format Solutions